

# THE AUTO-RANGE



New Auto Restart Pump Control

- Ideal for domestic pressure boosting or irrigation
- Complete pump assembly with a 1,5 meter cable and fitted with a SA plug
- Automatic start and stop on water demand
- Dry run protection

MODEL	VOLTAGE	ELECTRICAL DATA		HYDRAULIC DATA														
		kw	In A	Q=M <sup>3</sup> /H	0	0.3	0.6	0.9	1.2	1.8	2.4	3.0	3.6	4.8	6	7.2	9	9.6
				Q=l/min	0	5	10	15	20	30	40	50	60	80	100	120	150	160
KPF 30/16 M AUTO	1x230 V~	0,37	2,37	H	32.5	31	25	22	17.5	10								
JETCOM 82 M AUTO	1x220 - 240 V~	0,6	3,8		47	42	40	36	34	30	26.2	23.5	20					
K 20/41 M	1x220 - 240 V~	0.37	3								20.3	19.4	18	16.9	13.6	8.3		
K 30/70 M AUTO	1x220 - 240V~	0.75	6		31.8						29.5	28.9	25	27	24.2	19.8	13.5	
K 35/100 M AUTO	1x220 - 240 V~	1.1	7.1		38.5							37.5	37	36.5	35	32	28.5	18.5



RELIABILITY



SIMPLE INSTALLATION



PLUG & PLAY



WATER BOOSTING



GARDENING & IRRIGATION



IRRIGATION SYSTEMS



# OUT WITH THE OLD IN WITH THE NEW!



**PUMP CONTROL AUTO  
RESTART 1.1kW / 10A**

**PUMP CONTROL AUTO  
RESTART 2.2kW / 16A**



**EQUIPPED WITH A QUICK CHANGE PC BOARD CONSOLE,  
CABLES AND SA PLUG**

## Technical Information

PUMP CONTROL AUTO RESTART 1.1kW / 10A	
Input Voltage:	220-240V AC
Frequency:	50/60hz
Maximum Current:	10Amp
Start Pressure:	1.5 bar
Maximum Pressure:	10 bar
Maximum Working Temperature:	60 ° Celsius
Protection Rating:	IP65
Connection (inlet/outlet):	25mm

PUMP CONTROL AUTO RESTART 2.2kW / 16A	
Input Voltage:	220-240V AC
Frequency:	50/60hz
Maximum Current:	16Amp
Start Pressure:	2.2 bar
Maximum Pressure:	10 bar
Maximum working temperature:	60 ° Celsius
Protection Rating:	IP65
Connection (inlet/outlet):	32mm

Tel: +27 12 361 2603 | +27 12 361 3997

[www.dabpumps.co.za](http://www.dabpumps.co.za)

Twenty One Industrial Estate, 16 Purlin Street, Warehouse 4, Unit B,  
Olifantsfontein, South-Africa

